



**Specifications Bright Choice LED  
Downlight Round Tiltable 15W 1200lm  
60D - 930 Warm White | 135mm -  
Cutout 110mm - UGR <19**

[View Product](#)

## General Information

|                          |                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------|
| SKU                      | 245189                                                                                        |
| EAN                      | 8719157041874                                                                                 |
| Manufacturer Code        | 8719157041874                                                                                 |
| Brand                    | Bright Choice                                                                                 |
| Manufacturer Name        | White label LED Downlight Round Tiltable 15W 1200lm 60D 930 UGR19<br>CutoutØ110mm FrameØ135mm |
| Any Lamp all-in warranty | 2 Years                                                                                       |
| Average Lifetime (h)     | 20000                                                                                         |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | Yes               |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 75                |
| Wattage                     | 15W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 930 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 90-99             |
| Colour of Light             | White             |

|                          |                                |
|--------------------------|--------------------------------|
| Light colour options     | Single Color                   |
| Beam Angle (degree)      | 60                             |
| Luminous Flux (Lumen)    | 1200lm                         |
| Luminous Efficacy (lm/W) | 80                             |
| Installation Depth (mm)  | 75                             |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 110               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Colour of the Fixture  | White             |
| Colour of material     | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 75  |
| Diameter (mm) | 135 |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process